



KINETIC PROCESS
TECHNOLOGY INDIA PVT. LTD.

RAIKVA BUILDING

207, 3A, Rammohan Mullick Garden Lane. (Opp. Saltlake Stadium at Beleghata Building More) Kolkata 700 010

Email: Sales@kineticgroup.in Call: 062919 76424 | 99038 33205 Toll Free: 1800 3090 198



"CONTROLLED"
COLOUR SORTER
LAM DIFFERENT

ULTRA-HD PREMIUM SORTING TECHNOLOGY

Introducing
World's Best
SORTING
TECHNOLOGY
TO INDIA

World's 1st 4-color RGBW imaging

32% higher brightness in high cont 78% less color noise in low light



A deep inspection at the application lab of the results before bringing it to the market.

Kinetic ensures that all the new developments are thoroughly checked and verified before it is released to the market.

Every single grain is important to us and we do a deep analysis for the benefit of industry.



World's 1st RGBW Imaging Camera Technology in Colour Sorting.

Noise Reducer

1st time in colour sorting technology - around 80% noise reduction in low light.

Smart Vibrator

Intelligent Vibrators are capable of evenly spread the feed depending upon material availability. Intelligent vibrator absence of material.

Smart Multicolour Background LED

Intelligent Cloud Brain 1st time one touch intelligent

Multicolour background LED ensures much higher reflectivity and hence much better defect detection.

Smart Alarm

The most advanced colour alarm at TOP and SIDE assembly. On any event of fault registered, the TOP and SIDE alarm glows and changes the colours accordingly.

Smart Dust Handling Design

The Smart optical box design helps on almost nill loose dust on the viewing glass.

Extra Camera Machine has been designed in such a way that in future even IR cameras can be integrated.



Controlled Feed Controlled Light Controlled Air **Controlled Power**







Ultra HD - RGBW Enhanced Camera Technology has the best detection power which is backed by "NOISE REDUCER" feature results in purest form of detected signals which are processed as packages and ensures 100% receiving of signals through DUAL Parity Check Software and ejects only the defect grains.

A MARVAL PERFORMANCE! Unbelievable sorting performance with great product stability.

We are confident - you will rate this product as $\star\star\star\star\star\star$

TECHNICAL PARAMETERS

MODEL	Power (kw)	Dimension LxBxH (MM)	Weight (kg)
KZX 5	220V/50HZ	2360x1671x2044	1150
KZX 7	220V/50HZ	3040x1671x2044	1760
KZX 8	220V/50HZ	3380x1671x2044	2050
KZX10	220V/50HZ	4100x1671x2044	2800
KZX12	220V/50HZ	4640x1671x2044	3150

Remarks: * ±20mm Tolerance is acceptable by real calculation.



A committed SAS team behind